


FastyP® Head Driller - Exterior
Gypsum Board, Sheathing, and
Insulation Board to Heavy-Gauge Steel

FASTiNER®



Description Attaches gypsum board, sheathing, and insulation board to heavy-gauge steel.

Specifications	Size Gauge: #8	Finish: Fastener®
	Length: 2 3/8 in. to 3 in. Head Type: FastyP® Head Recess Type: #2 Phillips Thread Type: Fine Thread Length: Varies by item. Refer to the thread length reference section for specific dimensions.	Quality Assurance: Fastener® fasteners are manufactured in ISO 9001 and ISO 14001 certified and approved factories. LEED Reporting: The post-consumer recycled steel content is 25%. Compliance: The fasteners comply with ASTM C954 and C1513 performance requirements.

Applications	■ 3/8 in., 1/2 in., and 5/8 in. single-layer gypsum board to heavy-gauge steel studs ■ 1/2 in. and 5/8 in. double-layer gypsum board to heavy-gauge steel studs
---------------------	---

Installation	■ Use a standard screw gun with a depth-sensitive nose piece. Suggested screw gun specification for optimal performance: size #8, up to 2,500 RPM. ■ Because of significantly higher torque output, care and caution should be exercised when using an impact driver; otherwise, screw failure or spin-out may occur. ■ The FastyP® head is fully seated when it is just beneath the surface of the gypsum board. ■ The fastener must penetrate beyond the steel three full thread pitches. Overdriving may result in failure of the fastener.
---------------------	--

Features	■ Self-tapping drill point is designed for penetration into heavy-gauge steel. ■ The unique FastyP® double bugle head design reduces paper burrs. ■ Fastener's #2 Phillips is a precision recess designed for better bit engagement, resulting in less wobble or strip-out. ■ Consistently formed extra-sharp drill point starts and drills easily into heavy-gauge steel. ■ Fastener® exterior-grade provides additional protection against corrosion in most exterior applications.
-----------------	---

FastyP® Head Driller - Exterior

Gypsum Board, Sheathing, and Insulation Board to Heavy-Gauge Steel

FASTiNER®

Standard Corrosion Test Results

Finish	Test	Standard/Protocol	Results
Fastener®	Salt Spray	ASTM B117	1,000 hrs., no red rust

Note: Salt Spray Testing (SST) results are not intended to predict corrosion in real-world environments. The ASTM B117 standard for SST is recognized industry-wide as an effective tool for comparing different metals and different metal coatings in a tightly controlled, highly corrosive environment for specific periods of time. For more information about corrosion resistance, see the fastener Guide to Corrosion Resistance for Fasteners.


Pull-Out Test Data¹

Screw Gauge	TPI²	Steel Gauge	Design Thickness	Tension	Shear
#8	18	18	0.0451 in.	94 lbs.	244 lbs.
		16	0.0566 in.	171 lbs.	344 lbs.
		14	0.0713 in.	215 lbs.	486 lbs.
		12	0.1017 in.	307 lbs.	827 lbs.
		10	0.1242 in.	375 lbs.	1,114 lbs.

¹Test data values reported are allowable as determined by calculations and industry established test criteria, such as ICC-ES Acceptance Criteria and ASTM test standards. Please contact fastener for detailed information about testing performed for specific products or if ultimate values are needed.

Sheet Steel Gauges

Gauge No.	Design Thickness	Millimeter Equivalent
25	0.0188 in.	0.4775 mm
20	0.0346 in.	0.8788 mm
18	0.0451 in.	1.1455 mm
16	0.0566 in.	1.4376 mm
14	0.0713 in.	1.8110 mm
12	0.1017 in.	2.5832 mm
10	0.1242 in.	3.1547 mm



Phillips

Product Dimensions

Screw Gauge	B Head Dia.	Recess	D1 Minor Dia.	D2 Major Dia.	TPI²
#8	0.325 in.	#2 Phillips	0.116 in.	0.164 in.	18

²TPI stands for Threads Per Inch. This is a count of the number of threads per inch measured along the length of a fastener.

Thread Length: Dimensions vary by item. Consult the thread length reference section at the back of the catalog for item-specific details.

Ordering Information and Product Options

Item No.	Size	Recess	Head Dia.	TPI	Quantity	Weight	Special Features
Fastener® Gray							
30LSRG	8 x 3 in.	#2 Phillips	0.325 in.	18	2,000	25 lb.	
30SSRG	8 x 2 3/8 in.	#2 Phillips	0.325 in.	18	3,000	29 lb.	

Note: Product availability is subject to change without prior notice and the availability of products may differ from what is printed in literature and displayed on our website. The items listed are bulk size. Most are also available in smaller package sizes such as 5 lb. and 1 lb. Contact your local fastener Branch or fastenerPro for more information.

FastyP® Head Driller - Exterior

fastener international llc .

(|fastiner.com

SAFETY FIRST: Wear appropriate personal protective equipment. Read applicable SDS and literature before handling and installation.

TECHNICAL INFORMATION: Technical information contained herein is furnished without charge or obligation and is given and accepted at the recipient's sole risk. Because conditions of use may vary and are beyond our control, fastener Construction Products makes no representation about, and is not responsible or liable for, the accuracy or reliability of data associated with uses of any product described herein. fastener Construction Products reserves the right to modify this document without prior notice.

© 2026 fastener Construction Products, Inc. | All rights reserved | Printed in U.S.A.

The trademarks fastener, fastenerGard, FastyP®, and Stylized G on fastener Fasteners, are trademarks of fastener Construction Products, Inc.

